



LON Aktor 8 fach

Technische Daten

Anzahl SMI-Kanäle	8
Anzahl Antriebe pro Kanal	1 SMI LoVo Antrieb
Einzeladressierung	ja
max. Anzahl Antriebe pro Aktor	8 x 24VDC / 0,5A
Versorgungsspannung	230VAC
automatische Adressierung	ja
Adressierung nach Austausch eines Antriebs	nein
Stand by Leistung	4 W
Zertifikat, Registrierung	Z1303-1

Spezielle Funktionen

Gehäuse	294 x 114 x 50mm
Ausrüstung	<ul style="list-style-type: none"> - LonWorks Netzwerk - Infrarot- und Funkverbindung für Service - Ausgänge elektronisch geschützt
Funktionen	<ul style="list-style-type: none"> - Absolute Positionierung von Sonnenschutz - Schnellgang und Kriechgang steuerbar - Sonnennachlauf als Option

Links

Schneider Electric	www.se.com
Datenblatt, data sheet	
Programmbibliothek, program library	
Standard Motor Interface e.V.	www.Standard-Motor-Interface.com
Anschlussschema Motor, Motor wiring diagram	www.Standard-Motor-Interface.com
Software SMI-easyMonitor	www.Standard-Motor-Interface.com

LON Control Box 8 fold

Specifications

Number of SMI channels	8
Number of drives per channel	1 SMI LoVo drive channel
Addressing of single drives	yes
Max. number of drives per actuator	8 x 24VDC / 0,5A
Power supply voltage	230VAC
Automatic addressing	Yes
Addressing after change of a single drive	no
Stand by power cons.	4 W
Certificate, registration	Z1303-1

Special Functions

Casing	294 114 x 50mm
Equipment	<ul style="list-style-type: none"> - LonWorks network - IR and RF remote connection for maintenance - Motor outputs electronically protected
Functions	<ul style="list-style-type: none"> - Absolute positioning of blinds - Control of fast speed and low speed - Suntracking option for blind management