



KNX/SMI LoVo Aktor, 4 Kanäle, Broadcast

Technische Daten

Anzahl SMI-Kanäle	4
Anzahl Antriebe pro Kanal	4
Einzeladressierung	nein
max. Anzahl Antriebe pro Aktor	16
SMI-Antriebe	SMI LoVo
Versorgungsspannung galvanisch getrennt	ja
Isolationsspannung	4kV AC
automatische Adressierung	ja
Adressierung nach Austausch eines Antriebs	Nicht erforderlich
Zertifikat	Z2311-1, Rev. 1

Spezielle Funktionen

Bedienung am Aktor	<ul style="list-style-type: none"> • Auf/Ab • Schritt/Stop
Funktionen	<ul style="list-style-type: none"> • Auf/Ab • Schritt/Stop • 4 Preset-Positionen • 16 Szenen • Höhe 0...100% • Lamelle 0...100% • Wetteralarme • Sperren • Zwangsführung
Sonnenschutzautomatik	<ul style="list-style-type: none"> • Sonnenschutz • Heizen/Kühlen

Links

ABB STOTZ-KONTAKT GmbH
Datenblatt, Installationsanleitung usw.
Data sheet, installation manual etc.:

<https://new.abb.com/de/ueber-uns/gesellschaften/abb-stotz-kontakt>
<https://new.abb.com/products/de/2CDG110143R0011/sjr-s-4-24-2-1?DE>
<https://new.abb.com/products/2CDG110143R0011/sjr-s-4-24-2-1?DE>

SMI Standard Motor Interface e.V. :
Anschlussschema Motor / Wiring Diagram
Motor, Software SMI-EasyMonitor

www.Standard-Motor-Interface.com

KNX/SMI LoVo Actuator, 4 fold, broadcast

Specifications

Number of SMI channels	4
Number of drives per channel	4
Addressing of single drives	no
Max. number of drives per actuator	16
SMI drives	SMI LoVo
Power supply voltage galvanically isolated	yes
Insulation voltage	4kV AC
Automatic addressing	yes
Addressing after change of a single drive	Not required
Certificate	Z2311-1, Rev. 1

Special Functions

Manual operation	<ul style="list-style-type: none"> • Up/down • Step/stop
Functions	<ul style="list-style-type: none"> • Up/down • Step/stop • 4 presets • 16 scenes • Height 0...100% • Slat 0...100% • Weather alarms • Lock • Forced operation
Automatic sun protection	<ul style="list-style-type: none"> • Sun protection • Heating/cooling