



RP-C SMI LoVo Jalousiemodul

Technische Daten

Anzahl SMI-Kanäle	1
Anzahl Antriebe pro Kanal	16
Einzeladressierung	ja
max. Anzahl Antriebe pro Kanal	16
SMI-Antriebe	SMI LoVo
Versorgungsspannung	230 VAC, 50/60 Hz, 75 VA
automatische Adressierung	ja
Adressierung nach Austausch eines Antriebs	ja
Zertifikat	Z2009-1, Rev. 1

Spezielle Funktionen

Funktionen:	<ul style="list-style-type: none"> • Strom und Kommunikation über den RP-C Controller Raumbus • Ein SMI-Kanal, der in zwei Ausgänge aufgeteilt ist, zur SMI LoVo-Steuerung von 24-VDC-Jalousien (Öffnen, Schließen, Positionierung) • Vier Digitaleingänge • Wieland-Anschlüsse
Inbetriebnahme:	<ul style="list-style-type: none"> • Mobile app (Android und iOS)

RP-C SMI LoVo Blind Module

Specifications

Number of SMI channels	1
Number of drives per channel	16
Addressing of single drives	yes
Max. number of drives per channel	16
SMI drives	SMI LoVo
Power supply voltage	230 VAC, 50/60 Hz, 75 VA
Automatic addressing	yes
Addressing after change of a single drive	yes
Certificate	Z2009-1, Rev. 1

Special Functions

Functionality:	<ul style="list-style-type: none"> • Power and communications through RP-C controller room bus • One SMI channel, which is split into two outputs, for SMI LoVo control of 24 VDC powered blinds (opening, closing, positioning) • Four digital inputs • Wieland connectors
Commissioning:	<ul style="list-style-type: none"> • Mobile app (Android and iOS)

Links

Firma	www.se.com
Datenblatt, Installationsanleitung, Anwendungen usw.:	ecobuilding.schneider-electric.com
Data sheet, installation manual, application etc.:	ecobuilding.schneider-electric.com
SMI Standard Motor Interface e.V. :	www.Standard-Motor-Interface.com
Anschlusschema Motor / Wiring Diagram Motor, Software SMI-EasyMonitor	www.Standard-Motor-Interface.com